



WA. ALLOY CO.

WASHINGTON ALLOY'S Quality
Management System is
Certified to **ISO 9001:2008**
Cert # 05-R0925

4043 ALUMINUM Welding wire



Arc-Zone.com

ALLOY DESCRIPTION AND APPLICATION;

4043 is a 5% silicon aluminum filler recommended for

welding of 3003, 3004, 5052, 6061, 6063, and cast alloy such as 443, 355, 356 and 214.

TYPICAL GMAW WELDING PROCEDURES; DCEP

Wire Diameter	Amps	Volts	Travel speed (ipm)	Argon (cfh)
0.030	60-175	15-24	25-45	25-30
0.035	70-185	15-27	25-40	30-35
3/64	125-260	20-29	24-35	35-45
1/16	170-300	24-30	28-38	45-55
3/32	275-400	26-31	14-20	60-75

TYPICAL GTAW WELDING PROCEDURES; ACHF with Pure or Ziconiated Hemisphere shape tungsten tip

Filler Wire Size	Tungsten	Amps	Volts	Gas Cup Size	Argon (cfh)	Base thickness
1/16"	1/16"	60-80	15	3/8"	20	1/16"
3/32"	3/32"	125-160	15	3/8"	20	1/8"
1/8"	1/8"	190-220	15	7/16"	20	3/16"
5/32"	5/32"	200-300	15	1/2"	25	1/4"
3/16"	3/16"	330-380	15-20	5/8"	25	3/8"
1/4"	1/4"	400-450	25	5/8"	25	1/2"

Procedures are base on flat position and may vary with change in position, base metals, filler metals, equipment and other changes.

TYPICAL CHEMISTRY AND PROPERTIES;

Silicon	Iron	Copper	Manganese	Magnesium	Zinc	Titanium	Beryllium
4.5-6.0	0.80	0.30	0.05	0.05	0.10	0.20	0.0008
Aluminum Remainder and others each 0.50 & total 0.15				All values are maximum percentage unless noted			

Solidus:1065°F Liquidus:1170°F Density: 0.097 lbs./cu. In. Anodize color: Gray
Average Tensile Strength All weld metal (as welded) 29,000 psi (200 mpa)

AVAILABLE SIZES: TA 4043 = Spools of .023, .030, .035, .040, 3/64, 1/16

TB 4043 = Cut lengths of .023, .030, .035, 3/64, 1/16, 5/64, 3/32, 1/8, 5/32, 3/16, 1/4

SPECIFICATIONS; ANSI/AWS A5.10 ER/ R 4043
ASME SFA5.10 ER/ R 4043
AMS 4190

Other sizes available – please inquire

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.



Arc-Zone.com, Inc.

760-931-1500 – sales@arc-zone.com
2091 Las Palmas Drive, Ste. F – Carlsbad, CA 92011-1551 - USA