

CERTIFICATE of Compliance



American Welding Society

Quality Management System in accordance with ISO 9001:2000
Cert # 05-R0925

TRADE NAME: Low Fuming Bronze

Specification: AWS A 5.8 : ASME SFA 5.8 Classification: RBCuZn-C Also Known as LFB



Chemical Composition

	AWS Requirements		AWS Requirements	
Copper (Cu) (Ag)	56.0-60.0	Phosphorus (P)		
Zinc (Zn)	Remainder	Lead (Pb)	0.05 max. (O)	
Tin (Sn)	0.80-1.10	Aluminum (Al)	0.01 max. (O)	
Iron (Fe)	0.25-1.20	Silicon (Si)	0.04-0.15	
Manganese (Mn)	0.01-0.50			
Nickel (Ni) (Co)		Total other elements	0.50 max.	
^(Ag) Includes Silver ^(Co) Includes Cobalt ^(O) Included in other elements				

AWS Solidus, Liquidus and Brazing Temperature range for nominal composiition

Soldus	1590° F	·
Liqudus	1630° F	
Braze/welding range	1670-1750° F	
Tensile Strength Average	60-68,000 psi	
Brinell Hardness (HBW)	80-110	

The above table is for basic information only

This certification is provided by Washington Alloy Co. with the expressed understanding that if the product supplied fails to conform the stated specifications, there shall be no personal liability of any kind on the undersigned and the obligation and liability of Washington Alloy Co., with respect to such non-conformance or specification failure, shall be limited to a) an obligation to furnish the purchaser, at no additional charge, material that meets the specifications and conformances or b) to refund to the purchaser the full amount of money paid to Washington Alloy Co. for the return of the product in full. In no event shall Washington Alloy Co. be liable for consequential damage.

This certifies that the product supplied will meet the requirements of the noted classification and data above. Products supplied in accordance to the Quality Management System of Washington Alloy Company.



Certification Administrator

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.