

Turbo-4

TUNGSTEN ELECTRODE GRINDER

affordable • compact • safe

PROVIDES ALL THE FEATURES NECESSARY FOR GENERAL PURPOSE TUNGSTEN ELECTRODE GRINDING.



SPECIFICATIONS

Range of Included Angles 5° to 60°

Collet Diameters..... .040", 1/16", 3/32", 1/8"
 (1.0, 1.6, 2.4, 3.2mm)

Minimum Electrode Length 1.75" (45mm)
 (grinding shorter electrodes possible with collet accessory)

Voltage.....AC 100/110V 50/60 Hz

Power Rating60/70 Watts

Dimensions:

Length..... 7.00" (178mm)

Width..... 4.25" (108mm)

Height..... 4.75" (121mm)

Weight..... 4.0 lbs (1.82 kg)

CONTACT INFORMATION

Arc-Zone.com, Inc.

2091 Las Palmas Drive Ste. F

Carlsbad, CA 92011-1551

Tel. 1.760.931.1500/1.800.944.2243

Fax. 1.760.931.1504 Email: info@arc-zone.com



FEATURES

- ✓ Compact stable unit with durable design. No vibration.
- ✓ Longitudinal grinding for maximum arc stability.
- ✓ Measurement scales to create specifications for setup and grinding repeatability.
- ✓ Universal electrode collet handles electrode sizes .040" (1.0mm) - 1/8" (3.2mm).
- ✓ Handles a wide range of included angles.
- ✓ Offers the ability to grind compound angles.
- ✓ Electrode notching operation for simple cut-off.
- ✓ Grinds short electrodes.
- ✓ Measurement scale for shorter electrodes using optional short electrode tool.
- ✓ Detailed manual includes engineering data and welding recommendations.

